



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricant

**Uses advised against:** No uses advised against identified.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer / Supplier** Yamaha Motor Europe N.V.  
Koolhovenlaan 101  
1119 NC Schiphol-Rijk  
The Netherlands  
Telephone: +31 (0)20 6546000

**Contact Person:** Customer Support  
**E-mail:** P&Acustomersupport@yamaha-motor.nl

**1.4 Emergency telephone number:** UK NHS: Dial 111. Ireland NPIS: Dial +353 1 8092566.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

#### Classification according to Regulation (EC) No 1272/2008 as amended.

##### Physical Hazards

Aerosol	Category 1	H222: Extremely flammable aerosol. H229: Pressurized container: May burst if heated.
---------	------------	-----------------------------------------------------------------------------------------

##### Health Hazards

Acute toxicity (Inhalation - vapor)	Category 4	H332: Harmful if inhaled.
Skin irritation	Category 2	H315: Causes skin irritation.
Serious eye irritation	Category 2	H319: Causes serious eye irritation.
Specific Target Organ Toxicity - Single Exposure	Category 3	H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure	Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard	Category 1	H304: May be fatal if swallowed and enters airways.



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

---

**Environmental Hazards**

Chronic hazards to the aquatic environment

Category 3

H412: Harmful to aquatic life with long lasting effects.

**Hazard summary**

**Physical Hazards:** Flammable aerosol.

**Health Hazards**

**Skin Contact:** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**Ingestion:** If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

**2.2 Label Elements**

**Contains:** Xylene, mixed isomers  
Butanone  
Isopropyl alcohol  
base oil, low viscosity  
2-Butoxyethanol



**Signal Words:** Danger

**Hazard Statement(s):** H222: Extremely flammable aerosol.  
H229: Pressurized container: May burst if heated.  
H332: Harmful if inhaled.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H304: May be fatal if swallowed and enters airways.  
H412: Harmful to aquatic life with long lasting effects.



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

### Precautionary Statements

- Prevention:** P102: Keep out of reach of children.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Do not pierce or burn, even after use.  
P260: Do not breathe dust/fume/gas/mist/vapors/spray.  
P262: Do not get in eyes, on skin, or on clothing.  
P273: Avoid release to the environment.
- Response:** P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331: Do NOT induce vomiting.  
P312: Call a POISON CENTER or doctor/ physician if you feel unwell.
- Storage:** P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- Disposal:** P501: Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

### Supplemental label information

EUH066: Repeated exposure may cause skin dryness or cracking.

### 2.3 Information on other hazards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept.

### Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**General information:** Mixture of active ingredients with propellant

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
Xylene, mixed isomers	EC: 905-588-0	50,00% - <100,00%	01-2119539452-40	
Butanone	EINECS: 201-159-0	20,00% - <50,00%	01-2119457290-43	
Isopropyl alcohol	EINECS: 200-661-7	20,00% - <50,00%	01-2119457558-25	
base oil, low viscosity	EC: 920-750-0	10,00% - <25,00%	01-2119473851-33	
2-Butoxyethanol	EINECS: 203-905-0	1,00% - <5,00%	01-2119475108-36	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

**Classification**

Chemical name	Identifier	Classification
Xylene, mixed isomers	EC: 905-588-0	CLP: Flam. Liq. 3;H226, Acute Tox. 4;H312, Skin Irrit. 2;H315, STOT SE 3;H335, Acute Tox. 4;H332, Asp. Tox. 1;H304, Eye Irrit. 2;H319, STOT RE 2;H373
Butanone	EINECS: 201-159-0	CLP: , Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336 EUH066
Isopropyl alcohol	EINECS: 200-661-7	CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336
base oil, low viscosity	EC: 920-750-0	CLP: Flam. Liq. 2;H225, Asp. Tox. 1;H304, Aquatic Chronic 2;H411, STOT SE 3;H336
2-Butoxyethanol	EINECS: 203-905-0	CLP: Acute Tox. 4;H302, Acute Tox. 3;H331, Skin Irrit. 2;H315, Eye Irrit. 2;H319

CLP: Regulation No. 1272/2008.

**Acute Toxicity Estimate (ATE)**

Chemical name	Identifier	Exposure route		
		oral	dermal	Inhalation
2-Butoxyethanol	EINECS: 203-905-0	1.200 mg/kg		

**SECTION 4: First aid measures**

**General:** Instantly remove any clothing soiled by the product.

**4.1 Description of first aid measures**

- Inhalation:** Move to fresh air. Call a POISON CENTER or doctor/ physician if you feel unwell.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
- Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting. Call a POISON CENTER or doctor/ physician if you feel unwell.

**4.2 Most important symptoms and effects, both acute and delayed:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Causes serious eye irritation. Causes skin irritation. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Dizziness Freeze burns

**4.3 Indication of any immediate medical attention and special treatment needed** Get medical attention if symptoms occur.

**SECTION 5: Firefighting measures**



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

**5.1 Extinguishing media**

**Suitable extinguishing media:** CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Unsuitable extinguishing media:** Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture:**

Danger of explosion with aerosol cans.

**5.3 Advice for firefighters**

**Special fire-fighting procedures:** Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Ventilate closed spaces before entering them. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep away from sources of ignition - No smoking.

**6.2 Environmental Precautions:**

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

**6.3 Methods and material for containment and cleaning up:**

Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

**6.4 Reference to other sections:**

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

**SECTION 7: Handling and storage:**

**7.1 Precautions for safe handling:**

Minimize dust generation and accumulation. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Avoid contact with eyes. Wash hands thoroughly after handling. Avoid contact with skin. Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

**7.2 Conditions for safe storage, including any incompatibilities:** Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces. - No smoking.

**7.3 Specific end use(s):** Not applicable

**SECTION 8: Exposure controls/personal protection**

**8.1 Control Parameters**

**Occupational Exposure Limits**

Chemical name	Type	Exposure Limit Values	Source
Butanone	STEL	300 ppm 900 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
Butanone	TWA	200 ppm 600 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
Butanone	VME	200 ppm 600 mg/m3	France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984, as amended (01 2008)
Butanone	VLE	300 ppm 900 mg/m3	France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984, as amended (01 2008)
Isopropyl alcohol	VLE	400 ppm 980 mg/m3	France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984, as amended (01 2008)
2-Butoxyethanol	TWA	20 ppm 98 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
2-Butoxyethanol	STEL	50 ppm 246 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
2-Butoxyethanol	VLE	50 ppm 246 mg/m3	France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended (03 2016)
2-Butoxyethanol	VME	10 ppm 49 mg/m3	France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended (03 2016)

**Biological Limit Values**

Chemical name	Exposure Limit Values	Source
Butanone (MEK: Sampling time: End of shift.)	2 mg/l (Urine)	FR IBE (1997)

**8.2 Exposure controls**

**Appropriate engineering controls:** Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

---

**Individual protection measures, such as personal protective equipment**

- General information:** Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.
- Eye/face protection:** Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.
- Skin protection**  
**Hand Protection:** Material: Nitrile butyl rubber (NBR).  
Min. Breakthrough time:  $\geq 480$  min  
Recommended thickness of the material:  $\geq 0,38$  mm
- Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Other:** Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
- Respiratory Protection:** Respirator type: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information. Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
- Thermal hazards:** Not known.
- Hygiene measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
- Environmental Controls:** No data available.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**Appearance**

- Physical state:** Aerosol
- Form:** Aerosol
- Color:** No data available.
- Odor:** Characteristic
- pH:** substance/mixture is non-polar/aprotic substance/mixture is non-soluble (in water)



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

<b>Freezing point:</b>	not determined
<b>Boiling Point:</b>	not determined
<b>Flash Point:</b>	-97 °C
<b>Evaporation Rate:</b>	Not applicable for mixtures
<b>Flammability (solid, gas):</b>	not determined
<b>Explosion Limit - Upper (%):</b>	Not applicable for mixtures
<b>Explosion Limit - Lower (%):</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Relative vapor density:</b>	Not applicable for mixtures
<b>Density:</b>	0,74 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures
<b>Auto-ignition temperature:</b>	not determined
<b>Decomposition Temperature:</b>	not determined
<b>Kinematic viscosity:</b>	< 20,5 mm <sup>2</sup> /s (40 °C)
<b>Explosive properties:</b>	Value not relevant for classification
<b>Oxidizing properties:</b>	Value not relevant for classification
<b>Particle characteristics:</b>	Not applicable
<b>9.2 Other information</b>	No data available.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## SECTION 11: Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	Harmful if inhaled.
<b>Ingestion:</b>	No data available.
<b>Skin Contact:</b>	Causes skin irritation.
<b>Eye contact:</b>	Causes eye irritation.



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

---

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Oral

<b>Product:</b>	ATEmix: 20.000 mg/kg
<b>Specified substance(s)</b>	
Butanone	LD 50 (Rat): 3.300 mg/kg
Isopropyl alcohol	LD 50 (Rat): 4.570 mg/kg

##### Dermal

<b>Product:</b>	ATEmix: 2.200 mg/kg
<b>Specified substance(s)</b>	
Butanone	LD 50 (Rabbit): > 5.000 mg/kg
Isopropyl alcohol	LD 50 (Rabbit): 13.400 mg/kg

##### Inhalation

<b>Product:</b>	ATEmix: 18,59 mg/l
<b>Specified substance(s)</b>	
Isopropyl alcohol	LC 50 (Rat, 4 h): 30 mg/l

##### Skin Corrosion/Irritation:

**Product:** Based on available data, the classification criteria are met.

##### Serious Eye Damage/Eye Irritation:

**Product:** Based on available data, the classification criteria are met.

##### Respiratory or Skin Sensitization:

**Product:** Skin sensitizer: Based on available data, the classification criteria are not met.  
Respiratory sensitizer: Based on available data, the classification criteria are not met.

##### Germ Cell Mutagenicity

**Product:** Based on available data, the classification criteria are not met.

##### Carcinogenicity

**Product:** Based on available data, the classification criteria are not met.

##### Reproductive toxicity

**Product:** Based on available data, the classification criteria are not met.

##### Specific Target Organ Toxicity - Single Exposure

**Product:** Based on available data, the classification criteria are met.

##### Specific Target Organ Toxicity - Repeated Exposure

**Product:** Based on available data, the classification criteria are met.

##### Aspiration Hazard

**Product:** May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

---

**Endocrine disrupting properties**

**Product:** The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 12: Ecological information**

**General information:** Not applicable

**12.1 Toxicity**

**Acute toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Fish**

**Specified substance(s)**

Xylene, mixed isomers	LC 50 (Fish, 96 h): 2,6 mg/l
Butanone	LC 50 (Fish, 96 h): 3.220 mg/l
Isopropyl alcohol	LC 50 (Fish, 96 h): 9.640 mg/l

**Aquatic Invertebrates**

**Specified substance(s)**

Xylene, mixed isomers	EC 50 (Water Flea, 48 h): 3,82 mg/l
Butanone	EC 50 (Water Flea, 48 h): 5.091 mg/l
Isopropyl alcohol	LC 50 (48 h): 1.400 mg/l

**Chronic ToxicityProduct:** Based on available data, the classification criteria are met.

**Fish**

**Specified substance(s)**

Xylene, mixed isomers	NOEC (Fish, 56 d): > 1,3 mg/l
-----------------------	-------------------------------

**Aquatic Invertebrates**

**Specified substance(s)**

Xylene, mixed isomers	NOEC (Water Flea, 21 d): 1,57 mg/l
-----------------------	------------------------------------

**Toxicity to Aquatic Plants**

**Specified substance(s)**

Xylene, mixed isomers	EC 50 (Alga, 73 h): 4,36 mg/l
Butanone	EC 50 (Alga, 72 h): 1.972 mg/l (OECD 201)
Isopropyl alcohol	LC 50 (Alga, 72 h): > 100 mg/l

**12.2 Persistence and Degradability**

**Biodegradation**

**Product:** Not applicable for mixtures



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

---

**Specified substance(s)**

Xylene, mixed isomers	90 % (28 d, OECD 301F) Readily biodegradable
Butanone	98 % (28 d, OECD 301B)

**12.3 Bioaccumulative potential**

**Product:** Not applicable for mixtures

**12.4 Mobility in soil:**

**Product:** Not applicable for mixtures

**12.5 Results of PBT and vPvB assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Endocrine disrupting properties**

**Product:**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects:**

Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations**

---

**13.1 Waste treatment methods**

**General information:** Dispose in accordance with all applicable regulations.

**Disposal methods:** Discharge, treatment, or disposal may be subject to national, state, or local laws.

**SECTION 14: Transport information**

---

**ADR/RID**

14.1 UN number or ID number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
Hazard No. (ADR):	–
Tunnel restriction code:	(D)
14.4 Packing Group:	–
14.5 Environmental hazards:	–
14.6 Special precautions for user:	–



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

**IMDG**

- 14.1 UN number or ID number: UN 1950
- 14.2 UN Proper Shipping Name: AEROSOLS
- 14.3 Transport Hazard Class(es)
  - Class: 2.1
  - Label(s): 2.1
  - EmS No.: F-D, S-U
- 14.3 Packing Group: -
- 14.5 Environmental hazards: -
- 14.6 Special precautions for user: -

**IATA**

- 14.1 UN number or ID number: UN 1950
- 14.2 Proper Shipping Name: Aerosols, flammable
- 14.3 Transport Hazard Class(es):
  - Class: 2.1
  - Label(s): 2.1
- 14.4 Packing Group: -
- 14.5 Environmental hazards: -
- 14.6 Special precautions for user: -

**14.7 Maritime transport in bulk according to IMO instruments:** Not applicable.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

**EU. Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex I, Controlled Substances:** none

**EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended:** none

**Regulation (EC) No. 649/2012 Import and export of dangerous chemicals:** none

**15.2 Chemical safety assessment:** No Chemical Safety Assessment has been carried out.

**DIRECTIVE 2012/18/EU (SEVESO III) on the control of major-accident hazards involving dangerous substances**

Hazard category in accordance with Regulation (EC) No 1272/2008	Qualifying quantity for the application of Lower-tier requirements:	Qualifying quantity for the application of Upper-tier requirements:
P5c: P5c. Flammable liquids	5.000 t	50.000 t
P5a: P5a. Flammable liquids	10 t	50 t
P5b: P5b. Flammable liquids	50 t	200 t
H2: H2. Acute toxic	50 t	200 t



**Product name:** YAMALUBE CARBURETOR & INJECTOR CLEANER

**SECTION 16: Other information**

**Revision Information:** Vertical lines in the margin indicate an amendment.

**Wording of the H-statements in section 2 and 3**

EUH066	Repeated exposure may cause skin dryness or cracking.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H229	Pressurized container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Other information:** The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: - On the basis of test data - Calculation Method - Bridging Principle "Substantially similar mixtures" - Expert Judgement

**Revision Date:** 07.02.2024

**Disclaimer:** The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.